

Description

MAXFLUID Multi Silver Mono 40 & 50 oils use well-proven performance additives to fight wear, providing reliable lubrication and consistent performance.

They are suitable for day-to-day use in non-turbocharged engines. Performance level: API CC, SC.

Performance Features & Benefits

Reliable Performance

Provide reliable all-year-round performance in the applications for which they are intended.

Moderately Rated Diesel Engines

For use in less powerful diesel engines, such as those found in small trucks, commercial vehicles, vans, tractors, and certain stationary units.

Hydraulics & Transmissions

Can be used in certain transmission and mobile hydraulic systems where the use of monograde engine oils is recommended by the equipment manufacturer.

Applications

MAXFLUID Multi Silver Mono 40 & 50 is recommended for:

- Non-turbocharged diesel engines
- Small trucks, commercial vehicles, and vans
- Tractors
- Certain stationary diesel units
- Certain transmissions and mobile hydraulic systems where monograde engine oils are recommended by the equipment manufacturer

For a full listing of equipment approvals and recommendations, please contact MAXFLUID.

Product Advantages

- SAE 40 and SAE 50 monograde diesel engine oils
- Well-proven performance additives
- API CC, SC performance level
- Reliable wear protection
- Consistent all-year-round performance
- Suitable for day-to-day use in non-turbocharged engines
- Suitable for less powerful diesel engines
- Usable in certain transmissions and mobile hydraulics where recommended

TYPICAL PHYSICAL CHARACTERISTICS

PROPERTIES	UNIT	METHOD	Mono 40	Mono 50
SAE Viscosity Grade	-	-	40	50
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D445	136	211
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D445	14.1	19
Viscosity Index	-	ASTM D2270	100	101
Density @ 15°C	kg/l	ASTM D4052	0.895	0.900
Flash Point	°C	ASTM D92	250	252
Pour Point	°C	ASTM D97	-9	-9

The values shown are typical characteristics and may vary within normal manufacturing tolerances.

Health and Safety

MAXFLUID Multi Silver Mono 40 & 50 is a heavy-duty diesel engine oil intended for professional use. Under normal operating conditions and when handled in accordance with recommended practices, the product is not expected to present significant health or safety hazards.

Avoid prolonged or repeated skin contact and prevent contact with eyes. Wear appropriate personal protective equipment (PPE), including protective gloves and safety glasses, when handling the product. Ensure adequate ventilation in enclosed areas and avoid inhalation of oil mists.

Store in tightly sealed containers in a cool, dry, and well-ventilated area away from direct sunlight, excessive heat, and incompatible materials. Prevent spills from entering drains, waterways, or soil.

For detailed information regarding safe handling, storage, transportation, and disposal, refer to the latest Safety Data Sheet (SDS) for MAXFLUID Multi Silver Mono 40 & 50.